

# Better Pack® 500/500M

## ELECTRIC WATER-ACTIVATED TAPE DISPENSERS



### *Simple, Efficient and Durable*

The Better Pack 500 and 500M excel in medium-to-high volume packaging environments, especially when sealing random-sized cartons. The 500 is engineered for 115V and the 500M is engineered for 220V. Fourteen color-coded tactile preset buttons provide exceptional operational flexibility with a single touch. Since the dispensers are engineered to endure, these electronic workhorses stand up to rough handling and demanding work settings.

#### Fast and Efficient

- Tape output at 45" (114.3 cm) per second
- 14 color-coded keys offer one-touch dispensing of tape lengths from 6" to 45" (15.24 cm to 114.3 cm)
- Press and hold the Random key for custom tape lengths up to 120" (305 cm)
- Adjustable top heater warms the water, optimizing tape bonding

#### Rugged, Reliable and Safe

- Meets or exceeds UL, CE and CSA\* standards for operator and electrical safety
- Steel frame construction covered in durable ABS plastic
- Safety interlock switch disables cutting mechanism when cover is open, prevents worker injury
- Backed by the best industry warranty – 2 years parts and material; 6 months labor

Model #	Electrical Requirements	Preset Tape Length Range	Tape Width	Gum In or Gum Out (Tape)
500	115v	6" – 45" Plus up to 120" random lengths	1" to 3"	Gum In
500M	220v	15.24 cm – 114.3 cm Plus up to 305 cm random lengths	2.5 cm to 7.6 cm	Gum In or Gum Out

\* ETL Listed Mark Certification Completed. Certificate Copies Available Upon Request



# Better Pack® 500/500M



	Model	Specifications
Dimensions	BP500	18" L x 12" W x 10.5" H
	BP500M	45.7 cm x 30.5 cm x 26.7 cm
Shipping Weight	BP500	30 lbs.
	BP500M	13.6 kg
Maximum Roll Size	BP500	Up to 600' roll of tape; Up to 7.5" diameter
	BP500M	Up to 182.9 m roll of tape; Up to 16.51 cm diameter
Tape Width	BP500	1" to 3"
	BP500M	2.54 cm to 7.62 cm
Dispensing Speed	BP500	45"/second
	BP500M	114 cm/second
Water Bottle Capacity	BP500	44 ounces
	BP500M	1.3 liters
Electrical Requirements	BP500	115V, 60 Hz, 4 Amps
	BP500M	220V, 50 Hz, 2 Amps
Safety Compliance	BP500 BP500M	Meets or exceeds UL, CE and CSA standards*
Warranty	BP500 BP500M	2 years parts and materials, 6 months labor

\* ETL Listed Mark Certification Completed. Certificate Copies Available Upon Request