


PICK AND PLACE

TOP AND SIDE LOAD CASE PACKING



ALPHAPACK® 15/20
Integrated Case Erector and Bottom Sealer



ALPHAPACK® 8/10
Integrated Case Erector

PICK AND PLACE MODELS

SPECIFICATIONS	SPP	SPP DUAL	SPP HL	ALPHAPACK® 8	ALPHAPACK® 8 HD	ALPHAPACK® 10	ALPHAPACK® 15	ALPHAPACK® 20
Integrated Case Erector	N/A	N/A	N/A	Y	Y	Y	Y	Y
Bottom Case Sealing	N/A	N/A	N/A	N	N	N	Y	Y
Max. Speed	20 CPM	20 CPM	8 CPM	8 CPM	8 CPM	10 CPM	15 CPM	20 CPM
Max. Case Range	24" x 16" x 18"	24" x 16" x 18"	24" x 16" x 18"	24" x 16" x 18"	24" x 16" x 18"	24" x 16" x 18"	24" x 16" x 18"	28" x 16" x 18"
Min. Case Range	8" x 6" x 5"	8" x 6" x 5"	8" x 6" x 5"	8.5" x 4.75" x 4"	8.5" x 4.75" x 4"	8.5" x 4.75" x 4"	8" x 6" x 5"	8" x 6" x 5"
Magazine Capacity	N/A	N/A	N/A	50" ~150 Cases	50" ~150 Cases	50" ~150 Cases	50" ~150 Cases	50" ~150 Cases
Case Modification Available	N/A	N/A	N/A	N	N	N	Y	Y
Washdown Option	IP54	IP54	IP54	IP54	IP54	IP54	IP54	IP54
Glue Version	N/A	N/A	N/A	Y	Y	Y	N	N
Opposite Case Hand Option	N/A	N/A	N/A	N	N	N	Y	Y
Std. Voltage	240V/3PH	240V/3PH	240V/3PH	240V/3PH	240V/3PH	240V/3PH	240V/3PH	240V/3PH
SCFM - 80 PSI - 3/4 Supply Line	9-12 SCFM	9-12 SCFM	23 SCFM	30-90 SCFM	30-90 SCFM	30-90 SCFM	30-90 SCFM	30-90 SCFM
Footprint	9'7" x 6'6" x 10'7"	12' x 7'5" x 12'	14'3" x 5'8" x 11'10"	8'3" x 10'6" x 10'7"	8'3" x 10'6" x 10'7"	8'3" x 10'6" x 10'7"	13'6" x 10'7" x 7'4"	17'4" x 10'7" x 10'10"
Approx. Shipping Weight	~2500 lbs.	~3000 lbs.	~3000 lbs.	~4500 lbs.	~4500 lbs.	~4500 lbs.	~5000 lbs.	~5000 lbs.
Std. Finish	Steel Plus 316 is a two component, water base epoxy filled with 316 stainless steel flake. Finish Color is a Steel-It Grey and is USDA and FDA accepted.							
Controls	AB COMPACT LOGIX PLC with PV+ Color TS							
Available Options	Hand Pack Station, Low Case, Low Tape, Extended Magazine, Stack Lights, Elevation Kits, Change Part Carts, Spare Parts							