

# POWER TOOL OPTIONS

## Datasheet P328

Battery powered manual plastic strapping tool

Battery powered plastic strapping tool



### Characteristics

Strapping qualities:	Polyester (PET) and Polypropylene (PP) plain and embossed
Strapping dimensions:	width 12.0 – 16.0 mm thickness 0.40 – 1.05 mm / .016 – .041"
Weight incl. battery:	4.3 kg / 9.6 lbs
Tool size with battery:	L351 x W134 x H143 mm / 13.8" x 5.3" x 5.6"
Type of seal:	Friction weld sealing
Average seal strength:	approx. 75% (dependent on strap quality)
Tension force:	250 – 2600 N / 56 – 585 lbs (adjustable)
Tension speed:	67 – 124 mm/s / 2.6 – 4.9 inch/s
Power supply:	Battery Li-Ion 18VDC / 4.0 Ah
Suspension bracket:	optional

### Advantages

- High tension force up to 2600N / 585 lbs
- Tension force and sealing time adjustable with simple knobs
- Tool in both semi-automatic and automatic (single button) version available for efficient operation
- Brushless motor for less maintenance and improved life time
- Improved plates and guides – less effort to remove the tool from the strap
- No tension rocker – easier to remove tool from small package surfaces
- Motor temperature monitoring to protect motor from overheating
- Cycle counter included (special reader required)
- Battery well protected
- Battery charge indicator included
- Simple one-handed operation
- Tool is fully covered for finger protection
- Optional motor cooling fan available to reduce overheating risk

©Copyright PAC Strapping Products, Inc.