

# AUTOMATIC HEAVY DUTY COMBO SHRINK SYSTEM

MODEL: HDX250A



## FEATURES

### CONTROLS

- All Electric, No Air Required
- Schneider Electric PLC and Controls, Available Worldwide
- Variable Speed AC Motors
- 4.3" Color Touchscreen
- Store Up to 128 Recipes
- Multi-level Password Protection
- Multiple Language
- Two Emergency Stop Buttons
- Variable Speed and Temperature
- USB and SD Interface

### SEAL AREA

- 20" x 20", one piece blade
- Closing Conveyor
- Horizontal & Vertical Product Sensors
- Adjustable Seal Jaw Opening
- Adjustable Seal Pressure
- FDA Belts
- Slide On Overhead Film Cradle
- Overhead Scrap Rewind

### TUNNEL FEATURES

- 18" W x 10"H x 23"L Chamber
- Variable Speed Roller Conveyor

### OTHER FEATURES

- Compact Design
- Multiple Alarms for Machine Monitoring
- Powder Coated Steel Construction
- Locking Casters
- One Year Limited Warranty

HDX250A



## MODEL SPECS

SEAL AREA	20"W, 20"L (508mm W, 508mm L)
TUNNEL CHAMBER	18" W, 10" H, 23" L (458mm W, 254mm H, 585mm L)
FILM CAPACITY	23.5" W, 11.75"OD (600mm W, 300mm OD)
PRODUCTION RATE	0 – 20 PPM, Dependent upon product and film size
MAXIMUM PRODUCT DIMENSION	15.5" W, 16.5" L, 4.5" H (400mm W, 420mm L, 120mm H)
POWER REQUIREMENTS	208-240VAC, THREE PHASE, 22A
CONVEYOR HEIGHT	34.25" (870mm)
OVERALL DIMENSIONS	95" L, 47" W, 67" H (2390mm L, 1190mm W, 1680mm H)
WEIGHT	1496 Lbs. (677 Kg)