

MODEL C15-2000

Calender adapt for continuous fabrics:

- Transfer printing
- Direct inks reactivation
- Thermosetting – heatsetting

1. CHARACTERISTICS OF HEATING CYLINDER:

- 1.1. Diameter : 1.500 mm (59,05”).
- 1.2. Width : 2.000 mm (78,74”).
- 1.3. Working width: 1.800 mm (70,87”).

2. HEATING SYSTEM AND TEMPERATURE CONTROL:

- 2.1. The cylinder is heated by resistors (heating elements) in a vacuum sealed oil bath, in complete absence of air and pressure. MONTI ANTONIO S.p.A. system.
- 2.2. The temperature of the cylinder is set by a touch screen and is regulated by an electronic. The temperature control is equipped with an alarm system and a limitation system of maximum temperature (230 °C).

3. TENSION CONTROLS:

3.1. Tension control for printing material:

- Entry: axial unwinding with disk brake with pneumatic adjustment and fabric manual brake.
- Exit: double roll tangential winding, with possibility of soft or hard winding by transmission management, control by potentiometer.

3.2. Tension control for printing paper:

- Entry: axial unwinding with disk brake with pneumatic adjustment.
- Exit: axial winding with independent motor, adjustable by touch-screen.

3.3. Tension control for protection paper:

- Entry: axial unwinding with disk brake with pneumatic adjustment.
- Exit: axial winding with independent motor, adjustable by potentiometer.

4. OTHER DEVICES INTO MACHINE:

- 4.1. Independent motors with an electronic synchronization system.
- 4.2. NOMEX felt with pneumatic tension adjustment system and felt-centring device by means of motorized electric linear actuator.
- 4.3. Incorporated system for felt protection in case of black out and/or compressed air lack.
- 4.4. Multifunctional electronic meter-counter, with alarm to predetermine the length of production runs
- 4.5. Temperature cooling system for printed fabric exit, complete with fan.
- 4.6. General management of the machine, including temperature control by adjustable PLC for the memorization of production data.
- 4.7. Front touch-screen keyboard for production data access and programming.
- 4.8. Pneumatic movable paper separator.

5. ROLLS DIAMETER MACHINE WITHOUT OPTIONS:

- Fabric roll diameter in entry 400 mm (15,75”).
- Fabric roll diameter in exit 400 mm (15,75”).
- Printing paper roll diameter in entry 400 mm (15,75”) - Larger diameters on request.
- Printing paper roll diameter in exit 400 mm (15,75”) - Larger diameters on request.
- Protection paper roll diameter in entry 500 mm (19,68”).
- Protection paper roll diameter in exit 500 mm (19,68”).

All data and technical features are purely indicative, subjected to changes without prior notice and refer to standard machines without options

MODEL C15-2000

6. TECHNICAL DATA:
 - 6.1. Total Installed electrical power: 97 kW
 - 6.2. Average electric consumption: 65,5 kWh
 - 6.3. Power in ECONOMY MODE: 67 kW
 - 6.4. Compressed air pressure: 6-8 bar
 - 6.5. Mechanic speed: 1.5 ÷ 30 m/min
 - 6.6. Overall dimensions (with platform): width 3.620 mm (142,52"). length 4.220 mm (166,14"). height 2.590 mm (101,97").
 - 6.7. Net weight: 10.440 Kg
 - 6.8. Machine produced according to CE rules
 - 6.9. Customs tariff: 84 51 80 30

All data and technical features are purely indicative, subjected to changes without prior notice and refer to standard machines without options



MODEL C15-2600

Calender adapt for continuous fabrics:

- Transfer printing
- Direct inks reactivation
- Thermosetting – heatsetting

1. CHARACTERISTICS OF HEATING CYLINDER:

- 1.1. Diameter : 1.500 mm (59,05”).
- 1.2. Width : 2.600 mm (102,36”).
- 1.3. Working width: 2.400 mm (94,49”).

2. HEATING SYSTEM AND TEMPERATURE CONTROL:

- 2.1. The cylinder is heated by resistors (heating elements) in a vacuum sealed oil bath, in complete absence of air and pressure. MONTI ANTONIO S.p.A. system.
- 2.2. The temperature of the cylinder is set by a touch screen and is regulated by an electronic. The temperature control is equipped with an alarm system and a limitation system of maximum temperature (230 °C).

3. TENSION CONTROLS:

3.1. Tension control for printing material:

- Entry: axial unwinding with disk brake with pneumatic adjustment and fabric manual brake.
- Exit: double roll tangential winding, with possibility of soft or hard winding by transmission management, control by potentiometer.

3.2. Tension control for printing paper:

- Entry: axial unwinding with disk brake with pneumatic adjustment.
- Exit: axial winding with independent motor, adjustable by touch-screen.

3.3. Tension control for protection paper:

- Entry: axial unwinding with disk brake with pneumatic adjustment.
- Exit: axial winding with independent motor, adjustable by potentiometer.

4. OTHER DEVICES INTO MACHINE:

- 4.1. Independent motors with an electronic synchronization system.
- 4.2. NOMEX felt with pneumatic tension adjustment system and felt-centring device by means of motorized electric linear actuator.
- 4.3. Incorporated system for felt protection in case of black out and/or compressed air lack.
- 4.4. Multifunctional electronic meter-counter, with alarm to predetermine the length of production runs.
- 4.5. Temperature cooling system for printed fabric exit, complete with fan.
- 4.6. General management of the machine, including temperature control by adjustable PLC for the memorization of production data.
- 4.7. Front touch-screen keyboard for production data access and programming.
- 4.8. Pneumatic paper separator.

All data and technical features are purely indicative, subjected to changes without prior notice and refer to standard machines without options

MODEL C15-2600

5. ROLLS DIAMETER MACHINE WITHOUT OPTIONS:

- Fabric roll diameter in entry 400 mm (15,75").
- Fabric roll diameter in exit 400 mm (15,75").
- Printing paper roll diameter in entry 400 mm (15,75") - Larger diameters on request.
- Printing paper roll diameter in exit 400 mm (15,75") - Larger diameters on request.
- Protection paper roll diameter in entry 500 mm (19,68").
- Protection paper roll diameter in exit 500 mm (19,68").

6. TECHNICAL DATA:

- 6.1. Total Installed electrical power: 133 kW
- 6.2. Average electric consumption: 88,9kWh
- 6.3. Power in ECONOMY MODE: 91 kW
- 6.4. Compressed air pressure: 6-8 bar
- 6.5. Mechanic speed: 1.5 ÷ 30 m/min
- 6.6. Overall dimensions (with platform): width 4.220 mm (166,14"). length 4.220 mm (166,14"). height 2.590 mm (101,97").
- 6.7. Net weight: 13.650 Kg
- 6.8. Machine produced according to CE rules
- 6.9. Customs tariff: 84 51 80 30

All data and technical features are purely indicative, subjected to changes without prior notice and refer to standard machines without options



Calender adapt for continuous fabrics:

- Transfer printing
- Direct inks reactivation
- Thermosetting – heatsetting

1. CHARACTERISTICS OF HEATING CYLINDER:

- 1.1. Diameter : 1.500 mm (59,05”).
- 1.2. Width : 3.000 mm (118,11”).
- 1.3. Working width: 2.800 mm (110,24”).

2. HEATING SYSTEM AND TEMPERATURE CONTROL:

- 2.1. The cylinder is heated by resistors (heating elements) in a vacuum sealed oil bath, in complete absence of air and pressure. MONTI ANTONIO S.p.A. system.
- 2.2. The temperature of the cylinder is set by a touch screen and is regulated by an electronic. The temperature control is equipped with an alarm system and a limitation system of maximum temperature (230 °C).

3. TENSION CONTROLS:

- 3.1. Tension control for printing material:
 - Entry: axial unwinding with disk brake with pneumatic adjustment and fabric manual brake.
 - Exit: double roll tangential winding, with possibility of soft or hard winding by transmission management, control by potentiometer.
- 3.2. Tension control for printing paper:
 - Entry: axial unwinding with disk brake with pneumatic adjustment.
 - Exit: axial winding with independent motor, adjustable by touch-screen.
- 3.3. Tension control for protection paper:
 - Entry: axial unwinding with disk brake with pneumatic adjustment.
 - Exit: axial winding with independent motor, adjustable by potentiometer.

4. OTHER DEVICES INTO MACHINE:

- 4.1. Independent motors with an electronic synchronization system.
- 4.2. NOMEX felt with pneumatic tension adjustment system and felt-centring device by means of motorized electric linear actuator.
- 4.3. Incorporated system for felt protection in case of black out and/or compressed air lack.
- 4.4. Multifunctional electronic meter-counter, with alarm to predetermine the length of production runs.
- 4.5. Temperature cooling system for printed fabric exit, complete with fan.
- 4.6. General management of the machine, including temperature control by adjustable PLC for the memorization of production data.
- 4.7. Front touch-screen keyboard for production data access and programming.
- 4.8. Pneumatic paper separator.

5. ROLLS DIAMETER MACHINE WITHOUT OPTIONS:

- Fabric roll diameter in entry 400 mm (15,75”).
- Fabric roll diameter in exit 400 mm (15,75”).
- Printing paper roll diameter in entry 400 mm (15,75”) - Larger diameters on request.
- Printing paper roll diameter in exit 400 mm (15,75”) - Larger diameters on request.
- Protection paper roll diameter in entry 500 mm (19,68”).
- Protection paper roll diameter in exit 500 mm (19,68”).

All data and technical features are purely indicative, subjected to changes without prior notice and refer to standard machines without options

MODEL C15-3000

6. TECHNICAL DATA:

- 6.1. Total Installed electrical power: 157,8 kW
- 6.2. Average electric consumption: 105,3 kWh
- 6.3. Power in ECONOMY MODE: 107,8 kW
- 6.4. Compressed air pressure: 6-8 bar
- 6.5. Mechanic speed: 1.5 ÷ 30 m/min
- 6.6. Overall dimensions (with platform): width 4.620 mm (181,89"). length 4.220 mm (166,14"). height 2.590 mm (101,97").
- 6.7. Net weight: 14.000 Kg
- 6.8. Machine produced according to CE rules
- 6.9. Customs tariff: 84 51 80 30

All data and technical features are purely indicative, subjected to changes without prior notice and refer to standard machines without options



MODEL C15-3600

Calender adapt for continuous fabrics:

- Transfer printing
- Direct inks reactivation
- Thermosetting – heatsetting

1. CHARACTERISTICS OF HEATING CYLINDER:

- 1.1. Diameter : 1.500 mm (59,05”).
- 1.2. Width : 3.600 mm (141,73”).
- 1.3. Working width: 3.400 mm (133,86”).

2. HEATING SYSTEM AND TEMPERATURE CONTROL:

- 2.1. The cylinder is heated by resistors (heating elements) in a vacuum sealed oil bath, in complete absence of air and pressure. MONTI ANTONIO S.p.A. system.
- 2.2. The temperature of the cylinder is set by a touch screen and is regulated by an electronic. The temperature control is equipped with an alarm system and a limitation system of maximum temperature (230 °C).

3. TENSION CONTROLS:

3.1. Tension control for printing material:

- Entry: axial unwinding with disk brake with pneumatic adjustment and fabric manual brake.
- Exit: double roll tangential winding, with possibility of soft or hard winding by transmission management, control by potentiometer.

3.2. Tension control for printing paper:

- Entry: axial unwinding with disk brake with pneumatic adjustment.
- Exit: axial winding with independent motor, adjustable by touch-screen.

3.3. Tension control for protection paper:

- Entry: axial unwinding with disk brake with pneumatic adjustment.
- Exit: axial winding with independent motor, adjustable by potentiometer.

4. OTHER DEVICES INTO MACHINE:

- 4.1. Independent motors with an electronic synchronization system.
- 4.2. NOMEX felt with pneumatic tension adjustment system and felt-centring device by means of motorized electric linear actuator.
- 4.3. Incorporated system for felt protection in case of black out and/or compressed air lack.
- 4.4. Multifunctional electronic meter-counter, with alarm to predetermine the length of production runs.
- 4.5. Temperature cooling system for printed fabric exit, complete with fan.
- 4.6. General management of the machine, including temperature control by adjustable PLC for the memorization of production data.
- 4.7. Front touch-screen keyboard for production data access and programming.
- 4.8. Pneumatic paper separator.

5. ROLLS DIAMETER MACHINE WITHOUT OPTIONS:

- Fabric roll diameter in entry 400 mm (15,75”).
- Fabric roll diameter in exit 400 mm (15,75”).
- Printing paper roll diameter in entry 400 mm (15,75”) - Larger diameters on request.
- Printing paper roll diameter in exit 400 mm (15,75”) - Larger diameters on request.
- Protection paper roll diameter in entry 500 mm (19,68”).
- Protection paper roll diameter in exit 500 mm (19,68”).

All data and technical features are purely indicative, subjected to changes without prior notice and refer to standard machines without options

MODEL C15-3600

6. TECHNICAL DATA:

- 6.1. Total Installed electrical power: 188 kW
- 6.2. Average electric consumption: 125 kWh
- 6.3. Power in ECONOMY MODE: 128 kW
- 6.4. Compressed air pressure: 6-8 bar
- 6.5. Mechanic speed: 1.5 ÷ 30 m/min
- 6.6. Overall dimensions (with platform): width 5.220 mm (205,51"). length 4.220 mm (166,14"). height 2.590 mm (101,97").
- 6.7. Net weight: 16.425 Kg
- 6.8. Machine produced according to CE rules
- 6.9. Customs tariff: 84 51 80 30

All data and technical features are purely indicative, subjected to changes without prior notice and refer to standard machines without options

