CTac™ 80

White PB

Lindenmeyr Munroe

EVERYDAY SIGNAGE AND GRAPHICS

CTac™ 80 White PB is a versatile, printable monomeric PVC film designed for reliable performance across a wide range of applications. Available in gloss or matte finishes and coated with a permanent gray adhesive, it delivers strong adhesion on a variety of substrates.

With outdoor durability of up to three years, CTac™ 80 White PB is well suited for signage and general advertising applications, including window graphics, POP displays, stickers, and decals.

- IDEAL FOR INDOOR & OUTDOOR GENERAL SIGNAGE & DISPLAY
- WINDOW & WALL GRAPHICS
- SUITABLE FOR EVERYDAY APPLICATIONS

Product Codes:
CTMPB - CTac 80 White Matte PB
CTGPB - CTac 80 White Gloss PB

3.2 mil White Monomeric PVC

Matte or Gloss

(Eco) Solvent
Latex
UV

Grey
Permanent
Acrylic Solvent Adhesive

Widths up to 54 in

3 YEARS DURABILITY **INTERIOR & EXTERIOR**



APPLICATIONS

GENERAL SIGNAGE

WINDOW GRAPHICS

EXHIBITION GRAPHICS

POS DISPLAY



DRYTAC®
ADHESIVE SCIENCE

CTac™ 80

White PB

TECHNICAL SPECIFICATION

CTac™ 80 White PB films are 3.2 mil (80µ) gloss or matte white monomeric PVC films, coated on one side with a permanent pressure sensitive gray solvent acrylic adhesive that is protected by a 140gsm 2 side PE coated release liner. Suitable for interior and exterior use (up to 3 years).

CTMPB - CTac 80 White Matte PB
White Matte Film with Permanent Gray Adhesive

CTGPB - CTac 80 White Gloss PB
White Gloss Film with Permanent Gray Adhesive

- IDEAL FOR GENERAL SIGNAGE & GRAPHIC PROMOTIONS
- SUITABLE FOR INTERIOR AND EXTERIOR USE
- CAN BE APPLIED TO MANY SMOOTH SURFACES

INSTALLATION RECOMMENDATION
The surface must be clean and smooth and free of defects before application.

PRODUCT STRUCTURE

Film	White Gloss or Matte Monomeric PVC
Adhesive	Gray Permanent Solvent Acrylic (Pressure Sensitive)
Release Liner	140 gsm 2 Side PE Coated, 1 Side Siliconized White Kraft

PRODUCT CHARACTERISTIC

Film Thickness	3.2 mil (80µ)	4.2 mil (105µ)
Adhesive Layer	1 mil (25µ)	
Outdoor Durability	3 Years	
Application Temperature	>41˚F (5˚C)	
Service Temperature Range	-4˚F to 149˚F (-20˚C to 65˚C)	
Shelf Life	2 years	
Storage Conditions	59˚F to 72˚F (15˚C to 22˚C); 50 - 55% Relative Humidity	

OVERLAMINATE RECOMMENDATIONS

When using CTac™, an overlaminate can be used for maximum life expectancy. Products recommended for use with CTac™ are Drytac's Dynamic™ Plus, Interlam™ Pro or Protac™ overlaminates.

DRYTAC®
ADHESIVE SCIENCE

© 2025 Drytac Corporation. E&OE.
All other trademarks are the property of their respective owners.

12122025

Lindenmeyr Munroe

For more information, please contact your local Lindenmeyr Munroe sales representative.

LindenmeyrMunroe.com