Polar®

Lindenmeyr Munroe

Premium Air White Matte RB

COLD WEATHER, BUBBLE FREE TECHNOLOGY

Polar® Premium Air Removable is a high-quality printable self-adhesive vinyl designed for easy, bubble-free application and clean removal. Featuring Drytac's advanced bubble-free air release technology, this versatile solution ensures effortless installation, making it ideal for a wide range of temporary graphics, including retail displays, promotions, and event signage. Its removable adhesive allows for residue-free removal, providing flexibility without compromising on durability and print quality.



- IDEAL FOR INDOOR OR OUTDOOR EVENT SIGNAGE
- CAN BE USED FOR ARENA ADVERTISING
- SUITABLE FOR STICKERS AND DECALS

3.2 mil White Polymeric PVC — Matte

(Eco) Solvent
Latex
UV

Grey Removable Acrylic with Bubble-Free Technology

Widths up to 60 in

7 YEARS DURABILITY

EXTERIOR & INTERIOR
(With Matching Laminate; Up to 6 Months Removability)



APPLICATIONS

EVENT GRAPHICS

ARENA ADVERTISING

GENERAL SIGNAGE

DRYTAC®

ADHESIVE SCIENCE

Polar®

Premium Air White Matte RB

TECHNICAL SPECIFICATION

Polar® Premium Air White Matte RB is a 3.2 mil (80µ) premium, matte white polymeric self-adhesive PVC with a high quality, removable grey acrylic adhesive that is protected by a 90# PE Coated Kraft release liner with a bubble-free technology which makes for an easy install.

IDEAL FOR:

- RETAIL PROMOTIONS & POINT-OF-SALE DISPLAYS
- EVENTS & EXHIBITION GRAPHICS
- SHORT-TERM WALL & OFFICE DECOR

PRODUCT STRUCTURE

Film	Matte White Polymeric PVC
Adhesive	Grey Removable Acrylic (Pressure Sensitive)
Release Liner	90# PE Coated Kraft with Bubble-Free Technology

PRODUCT CHARACTERISTICS

Film Thickness	3.2 mil (80µ)
Adhesive Layer	1 mil (25µ)
	4.2 mil (105µ)
Film/Adhesive Ratio	3:2.1
Outdoor Durability	7 Years (With Matching Laminate; Up to 12 Months Removability)
Fire Ratings	Class A or Class 1 (ASTM E-84) PASS (CAN/ULC-S102)
Application Temperature	-4˚F (-20˚C)
Service Temperature Range	-20˚F (-29˚C) to 200˚F (93˚C)
Peel Strength (24 Hour Test)	10 ozf/in
Shelf Life	2 Years
Storage Conditions	59˚F to 72˚F (15˚C to 22˚C); 50 - 55% Relative Humidity

OVERLAMINATE RECOMMENDATIONS

When using Polar® Premium Air, an overlaminate can be used for maximum life expectancy. Products recommended for use are Drytac's Weathershield™ overlaminates.

DRYTAC®
ADHESIVE SCIENCE

© 2025 Drytac Corporation. E&OE.
All other trademarks are the property of their respective owners.

071322

Lindenmeyr Munroe

For more information, please contact your local Lindenmeyr Munroe sales representative.

LindenmeyrMunroe.com