PrintDuo™

Lindenmeyr Munroe

DOUBLE-SIDED PRINTABLE



PrintDuo™ is a premium double-sided printable white matte multilayered polypropylene and polyester film. The bright white surface of PrintDuo™ enhances vibrant color reproduction, ensuring crisp, sharp visuals and text that pop. Whether for indoor banner stands, roll-up displays, point-of-sale setups, or trade show graphics, it delivers professional, high-resolution results. It's also resistant to tearing and abrasion, ensuring your displays maintain their impressive look even in demanding environments.

What truly sets PrintDuo apart is its compatibility with Drytac's mounting adhesives such as SpotOn Duo, ReTac Duo and WindowTac. When paired, PrintDuo allows for the creation of double-sided window graphics that are easy to apply and reposition, thanks to the adhesive's combination of permanent and removable sides.

PRODUCT CODE: PRD

10 mil — **Multilayered Polypropylene and Polyester Blend** — **Matte**

(Eco) Solvent
Latex/Resin
UV

Adhesive Free

Widths up to 60 in

5 YEARS DURABILITY **INTERIOR**

2 YEARS DURABILITY **EXTERIOR**

APPLICATIONS

WINDOW GRAPHICS

WALL GRAPHICS

POS DISPLAY

HANGING BANNERS



DRYTAC® ZERO®

PrintDuo™

TECHNICAL SPECIFICATIONS

PrintDuo is a premium 10 mil (250µ) double-sided white matte blockout media, offering a PVC-free alternative for high-quality prints. Its unique composition of multilayered polypropylene and polyester provides exceptional strength and light-blocking properties, making it ideal for high-traffic commercial events, promotions, and display presentations.

- **DOUBLE-SIDED PRINTABLE:** IDEAL FOR CREATING IMPACTFUL, DUAL-SIDED DISPLAYS WITH VIBRANT COLORS AND SHARP DETAIL.
- **PVC-FREE CONSTRUCTION:** ENVIRONMENTALLY FRIENDLY, USING A BLEND OF POLYPROPYLENE AND POLYESTER FOR SUSTAINABLE SIGNAGE.
- **DURABLE & TEAR-RESISTANT:** BUILT TO WITHSTAND DEMANDING ENVIRONMENTS WITHOUT SACRIFICING PRINT QUALITY.
- **HIGH DIMENSIONAL STABILITY:** ENSURES ACCURATE, WARP-FREE PRINTING FOR LONG-LASTING DISPLAYS.

PRODUCT STRUCTURE

Film	Multilayered Polypropylene and Polyester Blend

PRODUCT CHARACTERISTICS

Film Thickness	10 mil (250µ)
Finish	Matte
Opacity	100%
Outdoor Durability	2 Years
ServiceTemperature Range	-4˚F to 146˚F (-20˚C to 63˚C)
Shelf Life	2 Years
Storage Conditions	59˚F to 72˚F (15˚C to 22˚C); 50 - 55% Relative Humidity

DRYTAC® ZERO®

© 2025 Drytac Corporation. E&OE.
All other trademarks are the property of their respective owners.

Lindenmeyr Munroe

For more information, please contact your local Lindenmeyr Munroe sales representative.

LindenmeyrMunroe.com