ReTac®

Textures

Lindenmeyr Munroe

ADDS VISUAL INTEREST TO ANY PRINT

ReTac® Textures can add depth and visual appeal to static, flat images with its embossed finish. With ReTac® on the back, eye-catching graphics printed on ReTac® Textures can easily be removed and repositioned multiple times without the worry of adhesive residue being left behind. This phthalate-free film can be easily applied, re-positioned and removed without surface damage or loss of adhesion. Available in Canvas, Linen, and Sand finishes.

- IDEAL FOR INTERIOR PROMOTIONS
- PERFECT FOR APPLICATION IN PUBLIC AREAS THAT REQUIRE COMPLIANCE WITH STRICT FIRE REGULATIONS
- CAN BE REMOVED WITHOUT LEAVING ADHESIVE RESIDUE

6 mil White Phthalate-Free Polymeric PVC — Matte

(Eco) Solvent
Latex
UV

ReTac® ultra removable and re-positionable adhesive

Widths up to 54 in

5 YEARS DURABILITY — **INTERIOR AND EXTERIOR** (2 YEAR REMOVABILITY EXTERIOR)







APPLICATIONS

Smooth Flat Surfaces

Point Of Sale Graphics

Interior Décor

Decals & Stickers

DRYTAC®
ADHESIVE SCIENCE

ReTac®

Textures

TECHNICAL SPECIFICATION

ReTac® Textures is a 150µ (6 mil) printable, matte white phthalate-free polymeric PVC film with ReTac® ultra removable adhesive. It has an embossed finish that adds depth and visual appeal to static, flat graphics. The texture helps draws attention to your image or message in a distinct and creative way.

- RETAC® TEXTURES IS A PHTHALATE-FREE FILM.
- IDEAL FOR WALL GRAPHICS, CUSTOM WALL MURALS, INTERIOR DÉCOR, RETAIL DISPLAYS, TRADE SHOW GRAPHICS AND SIGNAGE, AND TEXTURED LABELS.

Please Note: Plasticizer migration from some PVC substrates could cause adhesive residue being left behind upon removal, for more information please contact your local representative.

PRODUCT STRUCTURE

Film	Embossed Matte White Polymeric PVC
Adhesive	ReTac® ultra removable and re-positionable adhesive technology
Release Liner	143 gsm 2 Side PE Coated, 1 Side Solventless Siliconised Fine Paper

PRODUCT CHARACTERISTICS

Film Thickness	6 mil (150µ)
Adhesive Layer	1 mil (25µ)
	7 mil (175µ)
Outdoor Durability	5 years; 2 years removability
Fire Ratings	Class C-s1-d0 (EN-13501) Class 1 or A (ASTM E-84) PASS (CAN/ULC-S102)
Slip Ratings (ReTac Textures Sand) *for short-term indoor floor applications only	Moderate Slip Potential (EN 13036-4) Passed (ANSI A137.1/ A326.3) Dry: 58 Wet: 29 (AS HB198:2014 (AS/AZS 4586))
Application Temperature	>41˚F (5˚C)
Service Temperature Range	-40˚F to 120˚F (4.4˚C to 48.9˚C)
Shelf Life	2 years
Storage Conditions	59˚F to 72˚F (15˚C to 22˚C); 50 - 55% Relative Humidity

INSTALLATION RECOMMENDATION

Please see Wall Graphic Installation & Removal Instructions for further details. The surface must be clean and smooth & free of defects before application.

DRYTAC®
ADHESIVE SCIENCE

© 2021 Drytac Corporation. E&OE.
All other trademarks are the property of their respective owners.

03082021

Lindenmeyr Munroe

For more information, please contact your local Lindenmeyr Munroe sales representative.

LindenmeyrMunroe.com